



Stahlhandel Sebastian Sieler
Am Untergrün 11
79232 March-Buchheim
Tel 07665 / 20 30, Fax 07665 / 22 93
info@BSG-Stahlhandel.de
www.BSG-Stahlhandel.de

Blankstahl Lieferprogramm

Blankstahl Programm

	Seite
Rundstahl	
St 37 / S235	3 - 4
St 52.3 / S355	3 - 4
C 15	3 - 4
C 35	3 - 4
C 45	3 - 4
16 MnCr 5	3 - 4
42 CrMo 4 V / QT	3 - 4
11 SMn(Pb) 30 / 9 SMn(Pb) 28	5
C 45 geschliffen h6	6
ETG 100	7
Flachstahl	
St 37 / S235	8
C 45	9
St 52.3 / S355	10
11 SMnPb 30 / 9 SMnPb 28	11
Keilstahl C 45	12
Vierkantstahl	
St 37 / S235	13
C 45	13
St 52.3 / S355	13
11 SMn(Pb) 30 / 9 SMn(Pb) 28	13
Sechskantstahl	
St 37 / S235	14
C 35	14
C 45	14
11 SMnPb 30 / 9 SMnPb 28	14
Winkelstahl	15
T-Stahl; Dreikant-Stahl; U-Stahl	16

Blanker Rundstahl

kaltgezogen, Stablänge unter Ø 20 mm 3 mtr, ab Ø 20 mm 6 mtr
 DIN 671, h9, EN 10277/10278

Ø	kg/mtr	St 37 S235	St 52.3 S355	C 15	C 35	C 45	16 MnCr 5 1.7131	42 CrMo 4 1.7225 V
1	0,01	✓						
1,2	0,01	✓						
1,5	0,01	✓						
1,8	0,02	✓						
2	0,03	✓						
2,5	0,04	✓						
3	0,06	✓						
3,5	0,08	✓						
4	0,10	✓						
4,5	0,13	✓						
5	0,15	✓				✓		
5,5	0,19	✓						
6	0,22	✓	✓	✓	✓	✓	✓	
7	0,30	✓						
8	0,40	✓	✓	✓	✓	✓	✓	✓
9	0,50	✓				✓		
10	0,62	✓	✓	✓	✓	✓	✓	✓
11	0,75	✓				✓		
12	0,89	✓	✓	✓	✓	✓	✓	✓
13	1,04	✓				✓		
14	1,21	✓	✓	✓	✓	✓		✓
15	1,39	✓	✓	✓	✓	✓	✓	✓
16	1,58	✓	✓	✓	✓	✓	✓	✓
17	1,78	✓			✓	✓		
18	2,00	✓	✓	✓	✓	✓	✓	✓
19	2,23	✓						
20	2,47	✓	✓	✓	✓	✓	✓	✓
21	2,72	✓						
22	2,98	✓	✓	✓	✓	✓	✓	✓
23	3,26	✓						
24	3,55	✓	✓	✓	✓	✓	✓	✓
25	3,85	✓	✓	✓	✓	✓	✓	✓
26	4,17	✓	✓	✓	✓	✓	✓	
27	4,50	✓				✓		
28	4,83	✓	✓	✓	✓	✓	✓	✓
30	5,55	✓	✓	✓	✓	✓	✓	✓
32	6,31	✓	✓	✓	✓	✓	✓	✓
33	6,71					✓		

Blanker Rundstahl

kaltgezogen, Stablänge unter Ø 20 mm 3 mtr, ab Ø 20 mm 6 mtr
 DIN 671, h9, EN 10277/10278

Ø	kg/mtr	St 37 S235	St 52.3 S355	C 15	C 35	C 45	16 MnCr 5 1.7131	42 CrMo 4 1.7225 V
34	7,13	✓						
35	7,55	✓	✓	✓	✓	✓	✓	✓
36	7,99	✓	✓		✓	✓	✓	✓
38	8,90	✓	✓		✓	✓	✓	✓
40	9,87	✓	✓	✓	✓	✓	✓	✓
42	10,9	✓	✓		✓	✓		✓
45	12,5	✓	✓	✓	✓	✓	✓	✓
46	13,0	✓						✓
48	14,2	✓	✓	✓	✓	✓		✓
50	15,4	✓	✓	✓	✓	✓	✓	✓
52	17,3		✓	✓				
55	18,7	✓	✓	✓	✓	✓	✓	✓
58	20,7	✓			✓	✓		
60	22,2	✓	✓	✓	✓	✓	✓	✓
65	26,0	✓	✓	✓	✓	✓	✓	✓
70	30,2	✓	✓	✓	✓	✓	✓	✓
75	34,7	✓	✓	✓	✓	✓		
80	39,5	✓	✓	✓	✓	✓	✓	✓
85	44,5	✓	✓		✓	✓		
90	49,9	✓	✓		✓	✓		✓
95	55,6	✓			✓			
100	61,7	✓	✓		✓	✓		✓
105	68,0	✓	✓		✓			
110	74,6	✓	✓		✓	✓		
115	81,5	✓	✓		✓			
120	88,8	✓	✓		✓	✓		
125	96,3	✓	✓		✓	✓		
135	112		✓		✓			
130	104	✓			✓	✓		
140	121	✓			✓	✓		
150	139	✓			✓	✓		
155	148				✓			
160	158	✓			✓	✓		
170	178				✓			
180	200				✓			
190	223				✓			
200	247				✓			

11 SMn(Pb) 30 / 9 SMn(Pb) 28

DIN 671, h9, EN 10277/10278, Stablänge 3 mtr

Ø	kg/mtr
2	0,03
3	0,06
3,5	0,08
4	0,10
4,5	0,13
5	0,15
5,5	0,19
6	0,22
6,5	0,26
7	0,30
7,5	0,35
8	0,40
8,5	0,45
9	0,50
9,5	0,56
10	0,62
10,5	0,68
11	0,75
11,5	0,81
12	0,89
13	1,04
14	1,21
15	1,39
16	1,58
17	1,78
18	2,00
19	2,23
20	2,47
21	2,72
22	2,98
23	3,26
24	3,55
25	3,85
26	4,17
27	4,50
28	4,83
29	5,19
30	5,55
32	6,31

Ø	kg/mtr
33	6,71
34	7,13
35	7,55
36	7,99
38	8,90
40	9,87
42	10,9
45	12,5
46	13,0
48	14,2
50	15,4
52	17,3
55	18,7
56	19,3
58	20,7
60	22,2
63	24,5
65	26,0
70	30,2
75	34,7
80	39,5
85	44,5
90	49,9
95	55,6
100	61,7
105	68,0
110	74,6
115	81,5
120	88,8
125	96,3
135	112
130	104
140	121
150	139
155	148
160	158
180	200
200	247



Geschliffener Rundstahl

C 45 geschliffen und poliert, h6, DIN 59361, EN 10277/10278

Stablänge unter Ø 20 mm 3 mtr, ab Ø 20 mm 6 mtr

Ø	kg/mtr
4	0,10
5	0,15
6	0,22
8	0,40
10	0,62
11	0,75
12	0,89
14	1,21
15	1,39
16	1,58
17	1,78
18	2,00
20	2,47
22	2,98
25	3,85
28	4,83
30	5,55
32	6,31
35	7,55
40	9,87
45	12,5
50	15,4
55	18,7
60	22,2
65	26,0
70	30,2
75	34,7
80	39,5
90	49,9
100	61,7
120	88,8

teilweise auch in St 52 und C 35 lieferbar

ETG 100

DIN 668, h11, EN 10277/10278

Stablänge 3 mtr



Ø	kg/mtr
6	0,22
8	0,40
9	0,50
10	0,62
12	0,89
14	1,21
15	1,39
16	1,58
18	2,00
20	2,47
25	3,85
26	4,17
30	5,55
35	7,55
36	7,99
40	9,87
42	10,9
45	12,5
46	13,0
50	15,4
55	18,7
60	22,2
65	26,0
70	30,2

ETG 88 ist auch lieferbar

Blanker Flachstahl C 45

scharfkantig gezogen, DIN 174, h11, EN 10277/10278, Stablänge ca. 3 mtr

	3	4	5	6	8	10	12	14	15	16	18	20	25	30	32	35	40	50	60		
10	x	✓			✓															10	
12	x	✓																		12	
15	x			✓		✓	✓	✓												15	
16	x		✓																	16	
18	x					✓				✓										18	
20	x			✓	✓	✓	✓			✓	✓									20	
22	x					✓														22	
25	x			✓	✓	✓	✓	✓		✓	✓	✓	✓							25	
28	x				✓		✓													28	
30	x		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓					30	
32	x												✓	✓						32	
35	x		✓	✓	✓	✓	✓	✓		✓			✓		✓					35	
40	x			✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓				40	
45	x				✓	✓	✓	✓		✓		✓		✓				✓		45	
50	x			✓	✓	✓	✓	✓		✓		✓	✓	✓	✓	✓	✓			50	
55	x												✓							55	
60	x			✓	✓	✓	✓	✓		✓		✓	✓	✓	✓	✓	✓			60	
70	x					✓	✓	✓		✓		✓	✓	✓	✓	✓		✓	✓	✓	70
80	x					✓	✓	✓		✓		✓	✓	✓	✓	✓		✓	✓	✓	80
90	x						✓	✓		✓		✓		✓	✓	✓		✓	✓		90
100	x					✓	✓	✓	✓			✓		✓	✓	✓		✓	✓	✓	100
110	x										✓										110
120	x							✓			✓		✓	✓	✓	✓		✓	✓	✓	120
125	x							✓	✓										✓		125
130	x												✓								130
140	x											✓			✓						140
150	x									✓			✓		✓						150
160	x													✓		✓					160
180	x							✓							✓	✓					180
200	x							✓				✓		✓	✓	✓		✓	✓		200
220	x																	✓			220
250	x								✓										✓		250
300	x								✓										✓		300
	3	4	5	6	8	10	12	14	15	16	18	20	25	30	32	35	40	50	60		

Blanker Flachstahl St 52.3 / S355

scharfkantig gezogen, DIN 174, h11, EN 10277/10278

Stablänge 6 mtr

		10	12	15	20	25	30	35	40	50	
20	x	✓		✓							20
25	x	✓		✓	✓						25
30	x	✓	✓	✓	✓						30
35	x	✓		✓	✓						35
40	x	✓		✓	✓	✓	✓				40
50	x	✓		✓	✓	✓	✓	✓	✓		50
60	x	✓		✓	✓	✓	✓	✓	✓		60
70	x	✓		✓	✓		✓		✓		70
80	x	✓		✓	✓	✓	✓		✓	✓	80
90	x	✓		✓	✓						90
100	x	✓		✓	✓	✓	✓	✓	✓		100
		10	12	15	20	25	30	35	40	50	

Blanker Flachstahl 11 SMnPb 30

scharfkantig gezogen, DIN 174, h11, EN 10277/10278

Stablänge 3 mtr

		8	10	12	15	20	25	30	35	40	45	50	60	80	
20	x	✓	✓	✓	✓										20
25	x		✓	✓	✓	✓									25
30	x		✓	✓	✓	✓	✓								30
35	x			✓	✓	✓	✓	✓							35
40	x		✓	✓	✓	✓	✓	✓							40
45	x				✓	✓	✓	✓							45
50	x		✓	✓		✓	✓	✓	✓						50
60	x		✓	✓	✓	✓	✓	✓	✓	✓			✓		60
65	x							✓	✓						65
70	x							✓	✓	✓	✓				70
80	x					✓	✓	✓	✓	✓		✓	✓		80
90	x									✓		✓	✓		90
100	x					✓		✓		✓		✓	✓	✓	100
120	x			✓		✓		✓		✓		✓	✓		120
		8	10	12	15	20	25	30	35	40	45	50	60	80	

Blanker Keilstahl C 45

scharfkantig gezogen, DIN 6880, EN 10277/10278

Stablänge 3 mtr

	4	5	6	7	8	9	10	11	12	14	15	16	18	20	22	25	28	30	32	36	40	
4	x	✓																				4
5	x		✓																			5
6	x	✓		✓																		6
7	x				✓																	7
8	x		✓		✓	✓																8
10	x			✓		✓		✓														10
12	x			✓		✓		✓		✓												12
14	x			✓			✓				✓											14
15	x										✓											15
16	x				✓			✓		✓				✓								16
18	x					✓			✓					✓								18
20	x						✓		✓		✓					✓						20
22	x										✓						✓					22
25	x										✓							✓				25
28	x												✓									28
30	x																		✓			30
32	x												✓									32
36	x													✓								36
40	x														✓							40
45	x															✓						45
50	x																✓					50
56	x																		✓			56
63	x																			✓		63
70	x																				✓	70
80	x																				✓	80
	4	5	6	7	8	9	10	11	12	14	15	16	18	20	22	25	28	30	32	36	40	

Blanker Vierkantstahl

DIN 178, h11, EN 10277/10278

Stablänge 3 mtr, St 52.3 6 mtr

	kg/mtr	ST 37 S235	C 45	St 52.3 S355	9 SMn(Pb) 28 11 SMn(Pb) 30
2	0,03	✓			
2,5	0,05	✓			✓
3	0,07	✓			✓
4	0,13	✓	✓		
5	0,20	✓	✓		✓
6	0,28	✓	✓		✓
7	0,39	✓	✓		✓
8	0,50	✓	✓		✓
9	0,64	✓			✓
10	0,79	✓	✓		✓
11	0,95	✓			
12	1,13	✓	✓		✓
13	1,33	✓			
14	1,54	✓	✓		✓
15	1,77	✓	✓		✓
16	2,01	✓	✓		✓
17	2,27	✓			✓
18	2,54	✓	✓		✓
19	2,83				✓
20	3,14	✓	✓	✓	✓
22	3,80	✓	✓		✓
24	4,52	✓			✓
25	4,91	✓	✓	✓	✓
26	5,31				✓
27	5,72				✓
28	6,15	✓			✓
30	7,07	✓	✓	✓	✓
32	8,04	✓	✓		✓
35	9,62	✓	✓	✓	✓
36	10,2	✓	✓		✓
40	12,6	✓	✓	✓	✓
45	15,9	✓	✓	✓	✓
50	19,6	✓	✓	✓	✓
55	23,8	✓	✓		✓
60	28,3	✓	✓	✓	✓
65	33,2	✓	✓		✓
70	38,5	✓	✓	✓	✓
75	44,2	✓	✓		✓
80	50,2	✓	✓	✓	✓
85	56,7		✓		✓
90	63,6	✓	✓		✓
100	78,5	✓	✓		✓
110	95,0	✓			
120	113	✓			
150	177	✓			

Blanker Sechskantstahl

DIN 176, h11, EN 10277/10278


Stablänge 3 mtr



	kg/mtr	St 37 S235	C 35	C 45	9 SMn(Pb) 28 11 SMn(Pb) 30
5	0,17				✓
5,5	0,21				✓
6	0,24				✓
7	0,33			✓	✓
8	0,43			✓	✓
9	0,55	✓			✓
10	0,68	✓		✓	✓
11	0,82	✓			✓
12	0,98	✓		✓	✓
13	1,15	✓			✓
14	1,33	✓	✓	✓	✓
17	1,96	✓	✓	✓	✓
19	2,45	✓	✓	✓	✓
22	3,29	✓	✓	✓	✓
24	3,91	✓	✓	✓	✓
27	4,96	✓	✓	✓	✓
30	6,12	✓	✓	✓	✓
32	6,96	✓	✓	✓	✓
36	8,81	✓	✓	✓	✓
41	11,4	✓	✓	✓	✓
46	14,4	✓	✓	✓	✓
50	17,0	✓	✓	✓	✓
55	20,6	✓	✓	✓	✓
60	24,5	✓	✓	✓	✓
65	28,7	✓	✓	✓	✓
70	33,3	✓	✓	✓	✓
75	38,3			✓	✓
80	43,5	✓	✓	✓	✓
85	49,1		✓	✓	✓
90	55,1		✓	✓	✓
95	61,4		✓	✓	
100	68,0		✓	✓	
120	97,9			✓	

Blanker Winkelstahl scharfkantig gezogen

St 37 / S235, DIN 59370, EN 10277




gleichschenklig	kg/mtr
6 / 6 / 1,5 mm	0,19
6 / 6 / 2 mm	0,22
8 / 8 / 2 mm	0,25
10 / 10 / 2 mm	0,30
12 / 12 / 2 mm	0,35
12 / 12 / 3 mm	0,49
15 / 15 / 2 mm	0,44
15 / 15 / 3 mm	0,64
15 / 15 / 4 mm	0,82
20 / 20 / 2 mm	0,60
20 / 20 / 3 mm	0,87
20 / 20 / 4 mm	1,14
20 / 20 / 5 mm	1,38
25 / 25 / 2 mm	0,75
25 / 25 / 3 mm	1,11
25 / 25 / 4 mm	1,44
25 / 25 / 5 mm	1,77
30 / 30 / 2 mm	0,91
30 / 30 / 3 mm	1,34
30 / 30 / 4 mm	1,76
30 / 30 / 5 mm	2,18
35 / 35 / 3 mm	1,58
35 / 35 / 4 mm	2,07
35 / 35 / 5 mm	3,28
40 / 40 / 3 mm	1,81
40 / 40 / 4 mm	2,39
40 / 40 / 5 mm	2,94
40 / 40 / 6 mm	4,48
45 / 45 / 5 mm	3,34
50 / 50 / 3 mm	2,28
50 / 50 / 5 mm	3,73
50 / 50 / 6 mm	4,47
60 / 60 / 6 mm	5,42
70 / 70 / 8 mm	8,30
80 / 80 / 8 mm	9,66
80 / 80 / 10 mm	11,8
100 / 100 / 10 mm	14,9
120 / 120 / 12 mm	21,5
150 / 150 / 12 mm	27,0

ungleichschenklig	kg/mtr
15 / 10 / 3 mm	0,52
20 / 10 / 3 mm	0,64
20 / 15 / 3 mm	0,75
25 / 15 / 3 mm	0,87
30 / 15 / 3 mm	1,00
30 / 20 / 3 mm	1,11
30 / 20 / 4 mm	1,44
40 / 20 / 3 mm	1,34
40 / 20 / 4 mm	1,76
40 / 20 / 5 mm	2,18
45 / 30 / 4 mm	2,23
45 / 30 / 5 mm	2,77
50 / 30 / 5 mm	2,94
60 / 30 / 5 mm	3,37
60 / 40 / 5 mm	3,75
80 / 40 / 6 mm	5,41
80 / 40 / 8 mm	7,00
100 / 50 / 10 mm	11,7
130 / 65 / 10 mm	14,5
150 / 75 / 12 mm	20,0

Blanker T-Stahl

scharfkantig gezogen, EN 10277
 St 37 / S235




Breite		Höhe		Stärke	kg/mtr
20	/	20	/	3	0,88
25	/	25	/	3	1,15
30	/	30	/	4	1,77
35	/	35	/	4	2,07

Breite		Höhe		Stärke	kg/mtr
40	/	40	/	4	2,39
45	/	45	/	5	3,34
50	/	50	/	5	3,73

Blanker Dreikantstahl, gleichschenklig


scharfkantig gezogen, EN 10277
 St 37 / S235, Stablänge 3 mtr



Breite		Höhe		Stärke	kg/mtr
10	/	10	/	10	0,35
20	/	20	/	20	1,40

Blanker Dreikantstahl, rechtwinklig


scharfkantig gezogen, EN 10277
 St 37 / S235, Stablänge 3 mtr



Breite		Höhe		Stärke	kg/mtr
5	+ C /	5	/	7,05	0,10
7	/	7	/	9,90	0,20
10	/	10	/	14,10	0,40
15	/	15	/	21,15	0,90
20	/	20	/	28,30	1,57
30	/	30	/	42,43	3,53

Blanker U-Stahl

innen und außen scharfkantig gezogen, EN 10277
 St 37 / S235, Stablänge 3 mtr



Breite		Höhe		Stärke	kg/mtr
15	/	30	/	3	1,39
25	/	30	/	5	2,75
20	/	40	/	5	2,75
40	/	40	/	5	4,50
20	/	50	/	5	3,30

Breite		Höhe		Stärke	kg/mtr
40	/	60	/	5	5,10
45	/	80	/	8	10,0
50	/	100	/	8	11,9
40	/	120	/	8	11,9